

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00135 MST FURN PLSH FOR METAL 20net18

Material number : 00000000001001520

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers
For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION
Emergency Overview

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | light cream |
| Odour | characteristic |

GHS Classification

 Flammable aerosols : Category 2
 Gases under pressure : Liquefied gas
 Skin irritation : Category 2
 Skin sensitisation : Category 1

GHS Label element

Hazard pictograms :



Signal word : Warning

 Hazard statements : H223 Flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.

 Precautionary statements : **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects**Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous components**

| Chemical Name | CAS-No. | Concentration [%] |
|--|------------|-------------------|
| Distillates (petroleum), hydrotreated light (Vapour and gas) | 64742-47-8 | >= 10 - < 20 |
| propane | 74-98-6 | >= 5 - < 10 |
| butane | 106-97-8 | >= 1 - < 5 |
| Stoddard solvent | 8052-41-3 | >= 1 - < 5 |
| citral | 5392-40-5 | >= 0.1 - < 1 |

SECTION 4. FIRST AID MEASURES

General advice : Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

- advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|----------------------------------|---|-----------|
| Distillates (petroleum), hydrotreated light (Vapour and gas) | 64742-47-8 | TWA | 500 ppm 2,000 mg/m ³ | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m ³ | OSHA P0 |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | NIOSH REL |
| | | TWA | 1,000 ppm | OSHA Z-1 |

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

| | | | | |
|------------------|-----------|-----|--------------------------|-----------|
| | | | 1,800 mg/m3 | |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA P0 |
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m3 | NIOSH REL |
| | | TWA | 800 ppm 1,900 mg/m3 | OSHA P0 |
| Stoddard solvent | 8052-41-3 | TWA | 100 ppm | ACGIH |
| | | TWA | 350 mg/m3 | NIOSH REL |
| | | C | 1,800 mg/m3 | NIOSH REL |
| | | TWA | 500 ppm 2,900 mg/m3 | OSHA Z-1 |
| | | TWA | 100 ppm 525 mg/m3 | OSHA P0 |

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : light cream

Odour : characteristic

Odour Threshold : no data available

pH : no data available

Melting point/freezing point : no data available

Boiling point : no data available

Flash point :
no data available

Evaporation rate : no data available

Upper explosion limit : no data available

Lower explosion limit : no data available

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

| | |
|--|---------------------------|
| Vapour pressure | : no data available |
| Relative vapour density | : no data available |
| Density | : 0.938 g/cm ³ |
| Solubility(ies) | |
| Water solubility | : partly soluble |
| Partition coefficient: n-octanol/water | : no data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : no data available |
| Viscosity | |
| Viscosity, kinematic | : no data available |
| Heat of combustion | : 15.00 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : Oxidizing agents |
| Hazardous decomposition products | : Carbon dioxide (CO ₂) Carbon monoxide |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

no data available

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light (Vapour and gas):**propane:****butane:****Stoddard solvent:****citral:****STOT - single exposure**

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information**Product:**

Remarks: no data available

Components:**Distillates (petroleum), hydrotreated light (Vapour and gas):**

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

no data available

Persistence and degradability

no data available

Bioaccumulative potential**Product:**

Partition coefficient: n- : Remarks: no data available

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

octanol/water

Components:**butane :**Partition coefficient: n- : Pow: 2.89
octanol/water**citral :**Partition coefficient: n- : Pow: 2.76
octanol/water**Mobility in soil**

no data available

Other adverse effects

no data available

Product:

| | |
|------------|--|
| Regulation | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances |
|------------|--|

| | |
|---------|---|
| Remarks | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
|---------|---|

| | |
|-----------------------------------|---|
| Additional ecological information | : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects. |
|-----------------------------------|---|

Components:**Distillates (petroleum), hydrotreated light (Vapour and gas) :**

| | |
|-----------------------------------|---------------------|
| Additional ecological information | : no data available |
|-----------------------------------|---------------------|

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

| | |
|---------------------|--|
| Waste from residues | : Dispose of in accordance with local regulations. |
|---------------------|--|

| | |
|------------------------|--|
| Contaminated packaging | : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. |
|------------------------|--|

SECTION 14. TRANSPORT INFORMATION

| |
|---|
| Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY |
|---|

| |
|---|
| Transportation Regulation: IMDG (Vessel): |
|---|

SAFETY DATA SHEET



A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|-----------|--------------------|-----------------------------|
| xylenes | 1330-20-7 | 100 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Sudden Release of Pressure Hazard
Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL This product contains one or several components that are not on the Canadian DSL nor NDSL.
AICS Not in compliance with the inventory
NZIoC Not in compliance with the inventory
PICCS Not in compliance with the inventory
IECSC Not in compliance with the inventory

A00135 MST FURN PLSH FOR METAL 20net18


Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION
Further information
NFPA:

HMIS III:

| | |
|------------------------|----------|
| HEALTH | 3 |
| FLAMMABILITY | 3 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Warning:**

Hazard statements

: Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

A00135 MST FURN PLSH FOR METAL 20net18

Version 1.0

Revision Date 02/17/2015

Print Date 06/02/2015

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.