

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00374 MST ENGINE DEGREASER 20net16

Material number : 00000000001002335

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers**
**For SDS Information** : Compliance Services 1-877-428-9937

**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded

**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616

**SECTION 2. HAZARDS IDENTIFICATION**
**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	solvent-like

**GHS Classification**

Flammable aerosols : Category 2  
 Gases under pressure : Liquefied gas  
 Skin corrosion : Category 1B  
 Serious eye damage : Category 1  
 Germ cell mutagenicity : Category 1B  
 Carcinogenicity : Category 1A  
 Reproductive toxicity : Category 2

**GHS Label element**

Hazard pictograms :



Signal word : Danger

Hazard statements : H223 Flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H314 Causes severe skin burns and eye damage.  
 H340 May cause genetic defects.  
 H350 May cause cancer.  
 H361 Suspected of damaging fertility or the unborn child.

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

Precautionary statements : **Prevention:**  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P260 Do not breathe dust or mist.  
 P264 Wash skin thoroughly after handling.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P281 Use personal protective equipment as required.

**Response:**  
 P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P363 Wash contaminated clothing before reuse.

**Storage:**  
 P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**  
 P501 Dispose of contents/container in accordance with local regulation.

**Potential Health Effects**
**Carcinogenicity:**

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	cumene	98-82-8
<b>ACGIH</b>	Group 1: Carcinogenic to humans	
	benzene	71-43-2
	Confirmed animal carcinogen with unknown relevance to humans	
	2-butoxyethanol	111-76-2
<b>OSHA</b>	Confirmed human carcinogen	
	benzene	71-43-2
	OSHA specifically regulated carcinogen	
<b>NTP</b>	benzene	71-43-2
	Known to be human carcinogen	
	benzene	71-43-2

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 5 - < 10
2-butoxyethanol	111-76-2	>= 5 - < 10
2-aminoethanol	141-43-5	>= 1 - < 5
propane	74-98-6	>= 1 - < 5
2,2',2"-nitrilotriethanol	102-71-6	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
mesitylene	108-67-8	>= 1 - < 5
1,2,3-trimethylbenzene	526-73-8	>= 1 - < 5
Benzenesulfonic acid, C10-16-alkyl derivs.	68584-22-5	>= 1 - < 5
TEA Tallate	8043-27-4	>= 1 - < 5
sodium dodecylbenzenesulfonate	25155-30-0	>= 1 - < 5
tetrapotassium pyrophosphate	7320-34-5	>= 1 - < 5
Triethyl amine oleate	9680-30-2	>= 1 - < 5
toluene	108-88-3	>= 0.1 - < 1
benzene	71-43-2	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
Wash off immediately with plenty of water for at least 15 minutes.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.  
If in eyes, rinse with water for 15 minutes.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Always replace cap after use.  
 Dispose of rinse water in accordance with local and national regulations.  
 Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 No smoking.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.  
 Keep in a dry, cool and well-ventilated place.
- Materials to avoid : Oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm 120 mg/m <sup>3</sup>	OSHA P0
2-aminoethanol	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m <sup>3</sup>	NIOSH REL
		ST	6 ppm 15 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 6 mg/m <sup>3</sup>	OSHA Z-1
		STEL	6 ppm 15 mg/m <sup>3</sup>	OSHA P0
propane	74-98-6	TWA	3 ppm 8 mg/m <sup>3</sup>	OSHA P0
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL

# SAFETY DATA SHEET



## A00374 MST ENGINE DEGREASER 20net16

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

			1,800 mg/m3	
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
2,2',2"-nitrilotriethanol	102-71-6	TWA	5 mg/m3	ACGIH
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
mesitylene	108-67-8	TWA	25 ppm 125 mg/m3	NIOSH REL
1,2,3-trimethylbenzene	526-73-8	TWA	25 ppm 125 mg/m3	NIOSH REL
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0
benzene	71-43-2	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2
		PEL	1 ppm	OSHA CARC
		STEL	5 ppm	OSHA CARC

### Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g	ACGIH BEI
Remarks: Creatinine						
METHYLBENZENE	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
METHYLBENZENE		Toluene	Urine	End of shift (As soon as possible after	0.03 mg/l	ACGIH BEI

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

				exposure ceases)		
METHYLBENZENE		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g	ACGIH BEI
Remarks: Creatinine						
benzene	71-43-2	S-Phenylmercapturic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/g	ACGIH BEI
Remarks: Creatinine						
benzene		t,t-Muconic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.5 mg/g	ACGIH BEI
Remarks: Creatinine						

**Personal protective equipment**

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.  
Ensure that eyewash stations and safety showers are close to the workstation location.
- Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: solvent-like
Odour Threshold	: no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: not applicable
Evaporation rate	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: no data available
Solubility(ies)	
Water solubility	: completely soluble
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: no data available
Heat of combustion	: 16.50 kJ/g

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides



**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 2,968 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 10 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****sodium dodecylbenzenesulfonate:**

Acute oral toxicity : LD50 Oral rat: 438 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Extremely corrosive and destructive to tissue.

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Respiratory or skin sensitisation**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

no data available

**Reproductive toxicity**

no data available

**Solvent naphtha (petroleum), heavy arom.:**

**2-butoxyethanol:**

**2-aminoethanol:**

**propane:**

**2,2',2"-nitrilotriethanol:**

**butane:**

**1,2,4-trimethylbenzene:**

**mesitylene:**

**1,2,3-trimethylbenzene:**

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**Benzenesulfonic acid, C10-16-alkyl derivs.:****TEA Tallate:****sodium dodecylbenzenesulfonate:****tetrapotassium pyrophosphate:****Triethyl amine oleate:****toluene:****benzene:****STOT - single exposure**

no data available

**STOT - repeated exposure**

no data available

**Aspiration toxicity**

no data available

**Further information****Product:**

Remarks: no data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

no data available

**Persistence and degradability**

no data available

**Bioaccumulative potential****Product:**Partition coefficient: n-  
octanol/water : Remarks: no data available**Components:****Solvent naphtha (petroleum), heavy arom. :**Partition coefficient: n-  
octanol/water : log Pow: 4.2**2,2',2"-nitrilotriethanol :**Partition coefficient: n-  
octanol/water : Pow: 1**butane :**Partition coefficient: n-  
octanol/water : Pow: 2.89**toluene :**Partition coefficient: n-  
octanol/water : Pow: 2.73**Mobility in soil**

no data available

**Other adverse effects**

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

no data available

**Product:**

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

Waste from residues	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY
---

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity
--

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity
--

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity
---

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

**SECTION 15. REGULATORY INFORMATION**
**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sulphuric acid	7664-93-9	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Sudden Release of Pressure Hazard  
Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

1,2,4-trimethylbenzene	95-63-6	3.1722 %
benzene	71-43-2	0.1081 %

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.

cumene	98-82-8
benzene	71-43-2
naphthalene	91-20-3
2,2'-iminodiethanol	111-42-2

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
benzene	71-43-2

**The components of this product are reported in the following inventories:**

<b>TSCA</b>	On TSCA Inventory
<b>DSL</b>	All components of this product are on the Canadian DSL.
<b>AICS</b>	Not in compliance with the inventory
<b>NZIoC</b>	Not in compliance with the inventory
<b>PICCS</b>	Not in compliance with the inventory
<b>IECSC</b>	Not in compliance with the inventory

**Inventory Acronym and Validity Area Legend:**


**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**
**Further information**
**NFPA:**

**HMIS III:**

<b>HEALTH</b>	<b>3*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

**OSHA GHS Label Information:**

Hazard pictograms



Signal word

Hazard statements

**Danger:**  
Flammable aerosol. Contains gas under pressure; may explode if heated. Causes severe skin burns and eye damage. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child.

Precautionary statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust or mist. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. Use personal protective equipment as required.

**Response:** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/show er. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. IF exposed or concerned: Get medical advice/ attention. Wash contaminated clothing before reuse.

**Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:** Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

**A00374 MST ENGINE DEGREASER 20net16**

Version 1.0

Revision Date 03/04/2015

Print Date 06/02/2015

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.